

Roulement à aiguilles RNA6918-UU-IKO - RNA6918-UU-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/rna6918-uu-iko>

I KO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r_s (1)
105	—	—	RNA 6918UU	—	1 360	105	125	63	1.1
Standard mounting diameter D_s Max. mm		Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed (2) rpm					
118.5	172 000	471 000	1 800						

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	I KO
N° Ean13	3663952379791
Diam. intérieur	105 mm
Diam. extérieur	125 mm
Épaisseur	63 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE