

Roulement à aiguilles NA6901-U-IKO - NA6901-U-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/na6901-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
12	—	—	—	—	NA 6901U	45.5	12	24	22	23

r_s min (1)	F_w	Standard mounting dimensions (mm)			Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed(2)	Assembled inner ring
		Min.	Max.	Max.				
0.3	16	14	15	22	15 500	20 400	12 000	LRTZ 121623

Notes(1)
(1) Minimum allowable value of shaft diameter r
(2) Allowable rotational speed applies to grease lubrication.
Remark:
This outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381107
Diam. intérieur	12 mm
Diam. extérieur	24 mm
Épaisseur	23 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE