

Roulement à aiguilles NA6902-U-IKO - NA6902-U-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/na6902-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
15	—	—	—	NA 6902U	62.5	15	28	23	24

r_s min	F_w	Standard mounting dimensions (mm)			Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring
		Min.	Max.	Max.				
0.3	20	17	19	26	18 500	27 100	9 500	LRTZ 152024

Notes: (1) Minimum allowable value of shaft diameter r .
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381138
Diam. intérieur	15 mm
Diam. intérieur	0.591" inch
Diam. extérieur	28 mm
Diam. extérieur	1.102" inch
Epaisseur	24 mm
Epaisseur	0.945" inch
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE