

Roulement à aiguilles NA49-22-U-IKO - NA49-22-U-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/na49-22-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
22	—	NA 49/22U	—	—	87.5	22	39	17	18

r_s min (¹⁾)	F_w	Standard mounting dimensions (mm)			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring
		Min.	Max.	Max.				
0.3	28	24	27	37	18 300	23 700	7 000	LRTZ 222818

Note⁽¹⁾ Minimum allowable value of shaft diameter r
⁽²⁾ Allowable rotational speed applies to grease lubrication.
 Remark: The outer ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381251
Diam. intérieur	22 mm
Diam. intérieur	0.866" inch
Diam. extérieur	39 mm
Diam. extérieur	1.535" inch
Epaisseur	18 mm
Epaisseur	0.709" inch
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE