


## Roulement à aiguilles NA6905-U-IKO - NA6905-U-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/na6905-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
<b>25</b>	—	—	—	—	<b>NA 6905U</b>	162	25	42	30	31

$r_s$ min (1)	$F_w$	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating $C_0$ N	Allowable rotational speed(2) rpm	Assembled inner ring LRTZ 253031
		Min.	Max.	$d_s$				
0.3	30	27	29	40	39 200	58 700	6 500	

Notes(1)  
(1) Minimum allowable value of chamfer dimension r  
(2) Allowable rotational speed applies to grease lubrication.  
Remark:  
This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381312
Diam. intérieur	25 mm
Diam. extérieur	42 mm
Épaisseur	31 mm
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE