


Roulement à aiguilles NA4908-U-IKO - NA4908-U-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/na4908-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
40	—	NA 4908U	—	—	245	40	62	22	23

r _s min ⁽¹⁾	F _w	Standard mounting dimensions (mm)			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring
		d _s Min.	d _s Max.	D _s Max.				
0.6	48	44	47	58	37 200	58 400	4 000	LRTZ 404823

Notes: (1) Minimum allowable value of shaft diameter r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381503
Diam. intérieur	40 mm
Diam. intérieur	1.575" inch
Diam. extérieur	62 mm
Diam. extérieur	2.441" inch
Epaisseur	23 mm
Epaisseur	0.906" inch
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE