


Roulement à aiguilles NA6908-U-IKO - NA6908-U-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/na6908-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
40	—	—	—	—	NA 6908U	440	40	62	40	41

r_s min (1)	F_w	Standard mounting dimensions (mm)			Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed(2) rpm	Assembled inner ring
		Min.	Max.	D_w Max.				
0.6	48	44	47	58	63 700	117 000	4 000	LRTZ 404841

Notes(1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381510
Diam. intérieur	40 mm
Diam. extérieur	62 mm
Épaisseur	41 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE