

## Roulement à aiguilles NA4910-U-IKO - NA4910-U-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/na4910-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

| Shaft dia.<br>mm | Identification number |               |                |               | Mass<br>(Ref.) | Boundary dimensions<br>mm |     |     |     |
|------------------|-----------------------|---------------|----------------|---------------|----------------|---------------------------|-----|-----|-----|
|                  | With two seals        | With one seal | With two seals | With one seal |                | $r$                       | $d$ | $D$ | $C$ |
| 50               | —                     | NA 4910U      | —              | —             | 295            | 50                        | 72  | 22  | 23  |

  

| $r_s$ min<br>(1) | $F_w$ | Standard mounting dimensions (mm) |      |       | Basic dynamic load rating<br>$C$ | Basic static load rating<br>$C_0$ | Allowable rotational speed <sup>(2)</sup><br>rpm | Assembled inner ring |
|------------------|-------|-----------------------------------|------|-------|----------------------------------|-----------------------------------|--|----------------------|
|                  |       | Min.                              | Max. | $D_w$ |                                  |                                   |  |                      |
| 0.6              | 58    | 54                                | 57   | 68    | 41 300                           | 71 100                            | 3 500  | LRTZ 505823          |

Notes: (1) Minimum allowable value of chamfer dimension  $r$ .  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | IKO           |
| N° Ean13        | 3663952381589 |
| Diam. intérieur | 50 mm         |
| Diam. extérieur | 72 mm         |
| Épaisseur       | 23 mm         |
| Conditionnement | 1             |

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE