


Roulement à aiguilles NA6914-UU-IKO - NA6914-UU-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/na6914-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.)	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		β	d	D	C
70	—	—	NA 6914UU	—	1 400	70	100	54	55

r_s min	F_w	Standard mounting dimensions (mm)			Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed ⁽¹⁾	Assembled inner ring
		d_s Min.	d_s Max.	D_s Max.				
1	80	75	78	95	124 000	281 000	2 500	LRTZ 709055

Notes: (1) Minimum allowable value of shaft diameter r .
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381763
Diam. intérieur	70 mm
Diam. extérieur	100 mm
Épaisseur	55 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE