

Roulement à aiguilles BR303920-U-IKO - BR303920-U-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/br303920-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
47.625 (1 7/8)		BR 303920 U	202	47.625 (1 7/8)	61.912 (2 3/8)	31.750 (1 1/4)
Standard mounting dimensions mm		Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed ⁽²⁾		
D_1 Max.	F_{is} max	N	N	rpm		
54.7	1.5	48 500	82 100	4 000		

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952382296
Diam. intérieur	47.625 mm
Diam. extérieur	61.912 mm
Épaisseur	31.75 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE