

Roulement à aiguilles BR445628-U-IKO - BR445628-U-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/br445628-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series

| Shaft dia. mm (inch) | Identification number | | Mass (Ref.) g | Boundary dimensions mm(inch) | | |
|---------------------------------|-----------------------|------------------------------------|-----------------------------------|-------------------------------------------|----------------|----------------|
| | With two seals | With one seal | | F_w | D | C |
| 69.850 (2 3/4) | | BR 445628 U | 540 | 69.850 (2 3/4) | 88.900 (3 1/2) | 44.450 (1 3/4) |
| Standard mounting dimensions mm | | Basic dynamic load rating C_0 | Basic static load rating C_0 | Allowable rotational speed ⁽²⁾ | | |
| D_4 Max. | r_{as} max (1) | N | N | rpm | | |
| 80.7 | 2.0 | 98 700 | 189 000 | 2 500 | | |

Notes: (1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3663952382371 |
| Diam. intérieur | 69.85 mm |
| Diam. extérieur | 88.9 mm |
| Épaisseur | 44.45 mm |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE