

Roulement à aiguilles BRI61816-UU-IKO - BRI61816-UU-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/bri61816-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		d	D	C	B
9.525 (3/8)	BRI 61816 UU		79	9.525 (3/8)	28.575 (1 1/8)	25.400 (1)	25.650
F_w	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ^(*) rpm	Assembled inner ring LRBZ 61016 B
	Min.	Max.	$r_{as max}$ ^(*)				
	14	14.5	24.5	0.6	18 300	20 000	12 000

Notes: (*) Minimum allowable value of chamfer dimension r
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952382463
Diam. intérieur	9.525 mm
Diam. intérieur	3/8" inch
Diam. extérieur	28.575 mm
Diam. extérieur	1 1/8" inch
Epaisseur	25.4 mm
Epaisseur	1" inch
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE