


Roulement à aiguilles BRI284828-U-IKO - BRI284828-U-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/bri284828-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		g	d	D	C
44.450 (1 3/4)		BRI 284828 U	804	44.450 (1 3/4)	76.200 (3)	44.450 (1 3/4)	44.700
F_w	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRBZ 283628 B
	Min.	Max.	$r_{as max}$ ⁽¹⁾				
57.150 (2 1/4)	52.5	55	69.0	1.5	90 300	158 000	3 500

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952382715
Diam. intérieur	44.45 mm
Diam. extérieur	76.2 mm
Épaisseur	44.45 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE