


Roulement à aiguilles BRI325228-U-IKO - BRI325228-U-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/bri325228-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		g	d	D	C
50.800 (2)		BRI 325228 U	889	50.800 (2)	82.550 (3 $\frac{1}{4}$)	44.450 (1 $\frac{3}{4}$)	44.700
F_w	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed ^(*) rpm	Assembled inner ring LRBZ 324028 B
	Min.	Max.	$r_{as max}$ ^(†)				
63.500 (2 $\frac{1}{2}$)	58	61	74.3	1.5	94 600	174 000	3 000

Notes: (*) Minimum allowable value of chamber dimension r
(†) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952382722
Diam. intérieur	50.8 mm
Diam. extérieur	82.55 mm
Épaisseur	44.45 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE