


Roulement à aiguilles BRI325228-UU-IKO - BRI325228-UU-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/bri325228-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



| Shaft dia. mm (inch) | Identification number | | Mass (Ref.) g | Boundary dimensions mm(inch) | | | | |
|----------------------------|-----------------------------------|---------------|-----------------------------|---------------------------------------|--|--|----------------------|----------------------|
| | With two seals | With one seal | | g | d | D | C | B |
| 50.800 (2) | BRI 325228 UU | | 889 | 50.800 (2) | 82.550 (3 $\frac{1}{4}$) | 44.450 (1 $\frac{3}{4}$) | 44.700 | |
| F_w | Standard mounting dimensions (mm) | | | Basic dynamic load rating C N | Basic static load rating C_0 N | Allowable rotational speed ⁽²⁾ rpm | Assembled inner ring | |
| | Min. | Max. | $r_{as max}$ ⁽¹⁾ | | | | | |
| 63.500 (2 $\frac{1}{2}$) | 58 | 61 | 74.3 | 1.5 | 94 600 | 174 000 | 3 000 | LRBZ 324028 B |

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3663952382739 |
| Diam. intérieur | 50.8 mm |
| Diam. extérieur | 82.55 mm |
| Épaisseur | 44.45 mm |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE