


Roulement à aiguilles GBR223020-U-IKO - GBR223020-U-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/gbr223020-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series



| Shaft dia. mm (inch) | Identification number | | Mass (Ref.) g | Boundary dimensions mm(inch) | | |
|---------------------------------|-----------------------|--------------------------------|-------------------------------|---|----------------|----------------|
| | With two seals | With one seal | | F_w | D | C |
| 34.925 (1 3/8) | GBR 223020 UU | | 183 | 34.925 (1 3/8) | 47.625 (1 7/8) | 31.750 (1 1/4) |
| Standard mounting dimensions mm | | Ball dynamic load rating C_0 | Ball static load rating C_0 | Allowable rotational speed ^(*) | | |
| D_A | r as max | N | N | rpm | | |
| 42.8 | 0.6 | 49 500 | 91 800 | 2 500 | | |

Notes: (*) Minimum allowable value of chamfer dimension r .
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3663952382975 |
| Diam. intérieur | 34.925 mm |
| Diam. extérieur | 47.625 mm |
| Épaisseur | 31.75 mm |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE