


## Roulement à aiguilles GBR283720-UU-IKO - GBR283720-UU-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/gbr283720-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		$F_w$	$D$	$C$
<b>44.450</b> (1.75)	<b>GBR 283720 UU</b>		230	44.450 <sup>1)2)</sup>	58.738 <sup>2)3)</sup>	31.750 <sup>1)2)</sup>
Standard mounting dimensions mm		Ball dynamic load rating $C_0$	Ball static load rating $C_0$	Allowable rotational speed <sup>2)</sup>		
$D_A$	$r_{as\ max}$	N	N	rpm		
53.7	0.6	58 900	114 000	1 800		

Notes: 1) Minimum allowable value of chamfer dimension  $r$   
2) Allowable rotational speed applies to grease lubrication.  
Remark: This roller ring has an oil groove and an oil hole.  
3) Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952383033
Diam. intérieur	44.45 mm
Diam. extérieur	58.738 mm
Épaisseur	31.75 mm
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE