


## Roulement à aiguilles GBR303920-UU-IKO - GBR303920-UU-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/gbr303920-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		$F_w$	$D$	$C$
<b>47.625</b> (1 7/8)	<b>GBR 303920 UU</b>		240	47.625 (1 7/8)	61.912 (2 3/8)	31.750 (1 1/4)
Standard mounting dimensions mm		Ball dynamic load rating $C_1$	Ball static load rating $C_0$	Allowable rotational speed <sup>(*)</sup>		
$D_A$	$r_{as}$ max	N	N	rpm		
56.2	1	61 100	121 000	1 700		

Notes: (\*) Minimum allowable value of chamfer dimension  $r$   
(\*\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952383040
Diam. intérieur	47.625 mm
Diam. intérieur	1 7/8" inch
Diam. extérieur	61.912 mm
Diam. extérieur	2 7/16" inch
Epaisseur	31.75 mm
Epaisseur	1 1/4" inch
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE