


Roulement à aiguilles GBR567232-U-IKO - GBR567232-U-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/gbr567232-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
88.900 (3 1/2)	GBR 567232 U		1 240	88.900 (3 1/2)	114.300 (4 1/2)	50.800 (2)
Standard mounting dimensions mm		Ball dynamic load rating C_1	Ball static load rating C_0	Allowable rotational speed ^(*)		
D_A	r as max	N	N	rpm		
Max.	1.5	170 000	347 000	900		

Notes: (*) Minimum allowable value of chamfer dimension r
(*) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952383194
Diam. intérieur	88.9 mm
Diam. extérieur	114.3 mm
Épaisseur	50.8 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE