


## Roulement à aiguilles GBR607632-U-IKO - GBR607632-U-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/gbr607632-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		$F_w$	$D$	$C$
<b>95.250</b> (3 3/4)	<b>GBR 607632 U</b>		1 320	95.250 (3 3/4)	120.650 (4 7/8)	50.800 (2)
Standard mounting dimensions mm		Ball dynamic load rating $C_1$	Ball static load rating $C_0$	Allowable rotational speed <sup>(*)</sup>		
$D_A$ Max.	$r$ as max (°)	N	N	rpm		
112.6	1.5	175 000	371 000	850		

Notes: (\*) Minimum allowable value of chamfer dimension  $r$   
(°) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952383224
Diam. intérieur	95.25 mm
Diam. extérieur	120.65 mm
Épaisseur	50.8 mm
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE