


Roulement à aiguilles GBRI162820-U-IKO - GBRI162820-U-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/gbri162820-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		d	D	C
25.400 (1)	GBRI 162820 U		220	25.400 (1)	44.450 (1.75)	31.750 (1.25)

B	F_w	Standard mounting dimensions mm			$r_{as\ max}^{(1)}$	Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring
		Min.	Max.	Max.					
32.000	31.750 (1.25)	30.5	30.7	39.6	0.6	46 600	83 900	2 500	LRBZ 162020

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952383378
Diam. intérieur	25.4 mm
Diam. extérieur	44.45 mm
Épaisseur	31.75 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE