


Roulement à aiguilles GBRI183020-U-IKO - GBRI183020-U-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/gbri183020-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		<i>d</i>	<i>D</i>	<i>C</i>
28.575 (1 1/8)	GBRI 183020 U		240	28.575 (1 1/8)	47.625 (1 7/8)	31.750 (1 1/4)

<i>B</i>	<i>F_w</i>	Standard mounting dimensions mm			<i>r</i> _{as max} ⁽¹⁾	Basic dynamic load rating <i>C</i> N	Basic static load rating <i>C₀</i> N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring
		Min. <i>d_s</i>	Max. <i>d_s</i>	Max. <i>D_s</i>					
32.000	34.925 (1 3/8)	33.5	33.9	42.8	0.6	49 500	91 800	2 500	LRBZ 182220

Notes: (1) Minimum allowable value of chamfer dimension *r*.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952383385
Diam. intérieur	28.575 mm
Diam. intérieur	1 1/8" inch
Diam. extérieur	47.625 mm
Diam. extérieur	1 7/8" inch
Epaisseur	31.75 mm
Epaisseur	1 1/4" inch
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE