


Roulement à aiguilles TRU456430-IKO - TRU456430-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/tru456430-iko>

IKO
ROLLER BEARINGS
Caged Roller Bearings
Full Complement Roller Bearings



Shaft dia. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm					
	Full complement type	Caged type		d	D	C	r ⁽¹⁾ r _{s min}	J	E _w
45	—	TRU 456430	295	45	64	30	0.6	50.5	58.5
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾							
N	N	rpm							
32 600	59 700	8 000							

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952385396
Diam. intérieur	45 mm
Diam. extérieur	64 mm
Épaisseur	30 mm
Poids	320 g
Conditionnement	-
Norme	-

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE