


Roulement à aiguilles
NAU4922-IKO - NAU4922-IKO

https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/nau4922-iko



ROLLER BEARINGS
Caged Roller Bearings
Full Complement Roller Bearings



NAU4922 TRU

Shaft dia. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm					
	Full complement type	Caged type		d	D	C	^(*) r _s min	J	E _w
110	—	NAU 4922	1 930	110	150	40	1.5	123	138.5
Basic dynamic load rating C N Basic static load rating C₀ N Allowable rotational speed⁽²⁾ rpm									
113 000 200 000 3 500									

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r

⁽²⁾ Minimum rotational speed applies to grease lubrication.

Remark¹ The outer ring has an oil groove and an oil hole.

2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952385730
Diam. intérieur	110 mm
Diam. extérieur	150 mm
Epaisseur	40 mm
Conditionnement	1

contact@123roulement.ch
+33 359 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE