


Roulement à aiguilles TRU10013550-UU-IKO - TRU10013550-UU-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/tru10013550-uu-iko>

IKO
ROLLER BEARINGS
Caged Roller Bearings **[With Seal]**
Full Complement Roller Bearings **[With Seal]**



Shaft dis. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type			d	D	C	r ⁽¹⁾	J
100	—	TRU 10013550UU		1 900	100	135	50	1.5	112
E_w	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾ rpm						
125.5	N 124 000	N 264 000	1 700						

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
⁽²⁾ Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: 1. The NAU and NAG series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952386591
Diam. intérieur	100 mm
Diam. intérieur	3.937" inch
Diam. extérieur	135 mm
Diam. extérieur	5.315" inch
Epaisseur	50 mm
Epaisseur	1.969" inch
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE