


## Roulement à aiguilles NAS5017-ZZ-NR-IKO - NAS5017-ZZ-NR-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/nas5017-zz-nr-iko>

**IKO**  
**ROLLER BEARINGS**  
Roller Bearings for Sheaves



| Shaft dia. mm | Identification number |                            | Mass (Ref.) kg | Boundary dimensions mm                     |   |   |    |    |                |     |
|---------------|-----------------------|----------------------------|----------------|--|---|---|----|----|----------------|-----|
|               | Sealed type           | Shield type                |                | d  | D   | D <sub>2</sub>                                | B  | C  | C <sub>1</sub> | S   |
| 85            |                       | NAS 5017ZZNR               | 2.80           | 85   | 130                                       | 134.5   | 60 | 59 | 48             | 5.5 |
| <i>f</i>      | <i>c</i>              | <i>r</i> mm <sup>(1)</sup> | <i>J</i>       | Basic dynamic load rating C <sub>0</sub> N | Basic static load rating C <sub>0</sub> N | Allowable rotational speed <sup>(2)</sup> rpm |    |    |                |     |
| 2.5           | 2                     | 0.6                        | 101            | 257 000                                    | 446 000                                   | 1 200   |    |    |                |     |

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension *r*  
<sup>(2)</sup> Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
 Remarks: 1. The NAG and NAU series with a bore diameter, *d*, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
 2. The bearings with seals are provided with prepacked grease.

### CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | IKO           |
| N° Ean13        | 3663952386911 |
| Diam. intérieur | 85 mm         |
| Diam. extérieur | 130 mm        |
| Épaisseur       | 60 mm         |
| Conditionnement | 1             |

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE