

## Roulement à aiguilles NAXI923-IKO - NAXI923-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/naxi923-iko>

**LINEAR TYPE NEEDLE ROLLER BEARINGS**

Needle Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Bearings with Thrust Roller Bearing **With Inner Ring**

Identification number												
		Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g					
<b>NAXI</b>	<b>923</b>	49.5	—	—	—	—	—					
Boundary dimensions mm		Shoulder diameter mm		Basic dynamic load rating C		Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(1)</sup>		Assemble		
B	H	I <sub>1</sub>	r <sub>ms</sub>	r <sub>ms</sub>	d <sub>a</sub>	d <sub>b</sub>	Radial	Axial	Radial	Axial	rpm	
16	9	6.5	0.3	0.3	12	12	N	N	N	N		
		Min.		9 250		9 670		11 200		11 100		
										9 000		
										LRT		

Minimum allowable value of chamfer dimension r  
Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in IAX series, and a maximum of 25% of this value is allowable in the NBSX series.  
The outer ring has an oil groove and an oil hole.  
Grease is not prepacked. Perform proper lubrication.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952390666
Diam. intérieur	9 mm
Diam. extérieur	21 mm
Épaisseur	23 mm
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE