

## Roulement à aiguilles NAXI1223Z-IKO - NAXI1223Z-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/naxi1223z-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification Number						d	D	D <sub>1</sub>
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover			
12		<b>NAXI 1223Z</b>	56.5	—	—	—	12	24	28

  

Boundary dimensions mm				Lead-in chamfer mm	Basic dynamic load rating C	Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring						
D <sub>2</sub>	L	B	H			Radial	Radial			Radial					
25	23	16	9	6.5	0.3	0.2	10	18	9	8 230	10 000	9 190	11 100	9 500	LRT 71016

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Grease is not prepacked. Perform proper lubrication.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952390697
Diam. intérieur	12 mm
Diam. extérieur	24 mm
Épaisseur	23 mm
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE