

Roulement à aiguilles NBXI1223Z-IKO - NBXI1223Z-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/nbxi1223z-iko>

LINEAR TYPE NEEDLE ROLLER BEARINGS

Needle Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Bearings with Thrust Roller Bearing **With Inner Ring**

Identification number														
Mass (Ref.) g		With dust cover		Mass (Ref.) g		Mass (Ref.) g		With dust cover		Mass (Ref.) g		d		
---		---		---		NBXI 1223Z		63		12		12		
Boundary dimensions mm				Bore diameter mm		Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾		Assemble		
B	H	I_1	r_{max}	d_1	d_2	Radial	Axial	Radial	Axial	rpm		LRT 1		
16.5	9	6.5	0.3	0.3	15	15	26	14	12 300	10 200	14 900	23 900	14 000	LRT 1

Minimum allowable value of chamfer dimension r
Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in IAX series, and a maximum of 25% of this value is allowable in the NBXI series.
The outer ring has an oil groove and an oil hole.
Bearing is not prepacked. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952390710
Diam. intérieur	12 mm
Diam. extérieur	24 mm
Épaisseur	23 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE