

Roulement à aiguilles NAXI3030Z-IKO - NAXI3030Z-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/naxi3030z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing With Inner Ring
Needle Roller Bearings with Thrust Roller Bearing With Inner Ring

Shaft dia. mm	Identification Number						d	D	D ₁
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
30	NAXI 3030Z 215						30	47	52

Boundary dimensions mm				Lead-in chamfer mm	Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring	
D ₂	L	B	H			Radial	Radial			Axial
53	30	20	12	9	26 900	21 200	46 200	37 600	6 000	LRT 303520

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952390888
Diam. intérieur	30 mm
Diam. extérieur	47 mm
Épaisseur	30 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE