


Roulement à aiguilles NAXI3532Z-IKO - NAXI3532Z-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/naxi3532z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**



Shaft dia. mm	Identification Number						d	D	D ₁
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
35		NAXI 3532Z	273	—	—	—	35	52	60

Boundary dimensions mm				Bore chamfer mm	Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring				
D ₂	L	B	H			Radial	Radial			Axial			
61	32	20	13	10	52	39	29	400	26 900	54 100	50 000	5 500	LRT 354020

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952390932
Diam. intérieur	35 mm
Diam. intérieur	1.378" inch
Diam. extérieur	52 mm
Diam. extérieur	2.047" inch
Epaisseur	32 mm
Epaisseur	1.26" inch
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE