

Roulement à aiguilles NBXI4032-IKO - NBXI4032-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/nbxi4032-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Mass (Ref.) g		Mass (Ref.) g		Mass (Ref.) g		d	D	D ₁
	With dust cover	Without dust cover	With dust cover	Without dust cover	With dust cover	Without dust cover			
40	---	---	---	---	---	---	40	58	65

Identification Number: **NBXI 4032 344**

Boundary dimensions mm				Lead-in chamfer radius mm	Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring LRT 404520						
D ₂	L	B	H			Radial	Radial			Axial					
66.5	32	20	14	9	0.6	0.3	45	62	44	31 000	40 800	60 200	133 000	5 500	

Notes:
(1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952390987
Diam. intérieur	40 mm
Diam. extérieur	58 mm
Épaisseur	32 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE