


Roulement à aiguilles
NBXI4032Z-IKO - NBXI4032Z-IKO

https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/nbxi4032z-iko



COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing With Inner Ring

Needle Roller Bearings with Thrust Roller Bearing With Inner Ring

Identification Number													
Shaft dia. mm	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g	d	D	D ₁				
40	---	---	---	---	---	NBXI 4032Z	353	40	58	65			

Boundary dimensions mm				Bore mounting dimensions mm		Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRT 404520				
D ₂	L	B	H	I ₁	I ₂	Radial	axial	Radial	axial						
66.5	32	20	14	9	0.6	0.3	45	62	44	31 000	40 800	60 200	133 000	5 500	

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r

⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.

Remark 1: The outer ring has an oil groove and an oil hole.

2: Grease is not prepacked. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952390994
Diam. intérieur	40 mm
Diam. extérieur	58 mm
Epaisseur	32 mm
Conditionnement	1

contact@123roulement.ch
+33 359 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE