

Roulement à aiguilles NBXI4535Z-IKO - NBXI4535Z-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/nbxi4535z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Identification Number																					
Shaft dia. mm	Mass (Ref.) g		With dust cover		Mass (Ref.) g		With dust cover		Mass (Ref.) g	d	D	D ₁									
	45	---	---	---	---	---	---	---					NBXI 4535Z	396	45	62	70				
Boundary dimensions mm			Load limits mm		Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾		Assembled inner ring										
D ₂	L	B	H	I ₁	r _{min}	r _{max}	F _w	d ₄	d ₅	Radial	Axial	Radial	Axial	rpm	LRT 455025						
71.5	35	25	14	10	0.6	0.3	50	50	67	49	42	200	43	300	83	400	148	000	5	000	LRT 455025

Notes:
(1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.
Remarks:
Z: The outer ring has an oil groove and an oil hole.
2: Grease is not prepacked. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952391038
Diam. intérieur	45 mm
Diam. intérieur	1.772" inch
Diam. extérieur	62 mm
Diam. extérieur	2.441" inch
Epaisseur	35 mm
Epaisseur	1.378" inch
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE