

Roulement à aiguilles NAXI5040-IKO - NAXI5040-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/naxi5040-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification Number						d	D	D _i
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
50	NAXI 5040	582	—	—	—	—	50	72	85

Boundary dimensions mm				Lead-in chamfer mm	Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRT 506025						
D ₂	L	B	H			Radial	Radial			Axial					
86.5	40	25.5	17	12	1	1	60	75	59	47 500	41 400	103 000	89 700	4 000	LRT 506025

Notes:
(1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.

Remarks:
1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952391045
Diam. intérieur	50 mm
Diam. extérieur	72 mm
Épaisseur	40 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE