

Rotule GE GE220ES-IKO - GE220ES-IKO

<https://www.123roulement.ch/roulement-palier/rotule/ge/ge220es-iko>

SPHERICAL BUSHINGS
steel Spherical Bushings

Identification number		Mass (Ref.)	Boundary dimensions mm						Permissible
Without seals	With seals	M_0	d	D	B	C	d_k	$r_{1s \text{ min}}$	$r_{2s \text{ min}}$
GE 220ES		36.1	220	320	135	100	275	1.1	1.1

Mounting dimensions mm			Dynamic load capacity	Static load capacity
Max. ⁽¹⁾	Max.	Min.	C_d	C_s
			N	N
239.5	313	269	2 700 000	16 200 000

Minimum allowable value of chamfer dimensions r_1 and r_2
When Spherical Bushings are used with full fitting angle, the shaft shoulder dimension must be less than the maximum value.
The inner ring and the outer ring have an oil groove and two oil holes, respectively.
Not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952392080
Diam. intérieur	220 mm
Diam. extérieur	320 mm
Épaisseur	135 mm
Type	GE
Lubrification	sans
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE