


## Rotule GE GE80GS-IKO - GE80GS-IKO

<https://www.123roulement.ch/roulement-palier/rotule/ge/ge80gs-iko>

IKO

### SPHERICAL BUSHINGS

Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d	D	B	C	d <sub>s</sub>	r <sub>1</sub> <sup>(1)</sup>	r <sub>2</sub> <sup>(1)</sup>	α	α <sub>1</sub>
80	GE 80GS		3.60	80	130	75	50	115	1	1	14	13
Mounting dimensions mm		Dynamic load capacity C <sub>d</sub>		Static load capacity C <sub>s</sub>								
d <sub>s</sub>	D <sub>s</sub>											
Min.	Max. <sup>(2)</sup>	Max.	Min.	N	N							
85.5	87	124.5	112	564 000	3 380 000							

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimensions r<sub>1</sub> and r<sub>2</sub>.  
<sup>(2)</sup> When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d<sub>s</sub>.  
 Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
 2. Not provided with prepacked grease. Perform proper lubrication for use.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952392462
Diam. intérieur	80 mm
Diam. intérieur	3.15" inch
Diam. extérieur	130 mm
Diam. extérieur	5.118" inch
Epaisseur	75 mm
Epaisseur	2.953" inch
Type	GE
Lubrification	sans
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE