

Rotule GE

SBB76-2RS-IKO - SBB76-2RS-IKO

<https://www.123roulement.ch/roulement-palier/rotule/ge/sbb76-2rs-iko>

IKO
SPHERICAL BUSHINGS
 Steel-on-steel Spherical Bushings Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) kg	Boundary dimensions mm(inch)			
	Without seal	With seals		d	D	B	C
120.650 (4 7/8)		SBB 76-2RS	11.6	120.650 (4 7/8)	187.325 (7 1/2)	105.56 (4.156)	90.47 (3.562)
Radial internal clearance mm Min./Max.	Mounting dimensions mm		Dynamic load capacity C _d N	Static load capacity C _s N			
	d _k	d _j r ₁ max. r ₂ max.		C _d	C _s		
173(6.811)	0.13 / 0.23	136.8 0.8 1.1	1 530 000	9 210 000			

Notes:
 (1) Minimum allowable value of chamfer dimensions r₁ and r₂.
 (2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_k.
 Remark 1: The inner ring and the outer ring have an oil groove and two oil holes, respectively.
 2: Not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952393070
Diam. intérieur	120.65 mm
Diam. extérieur	187.325 mm
Epaisseur	105.56 mm
Type	-
Poids	11600 g
Lubrification	-
Conditionnement	-
Norme	-

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE