


Rotule GE SBB96-IKO - SBB96-IKO

<https://www.123roulement.ch/roulement-palier/rotule/ge/sbb96-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) kg	Boundary dimensions mm(inch)			
	Without seal	With seals		d	D	B	C
152.400 (6)	SBB 96		17.6	152.400 (6)	222.250 (8 7/8)	120.65(4.750)	104.78(4.125)
d_k	Radial internal clearance mm		Mounting dimensions mm		Dynamic load capacity C_d N	Static load capacity C_s N	
	Min.	Max.	d_1	r_1 Max. r_2 Max.			
207(8.150)	0.13	0.23	167.5	0.8 1.1	2 130 000	12 800 000	

Notes:
(1) Minimum allowable value of chamfer dimensions r_1 and r_2 .
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_k .
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952393100
Diam. intérieur	152.4 mm
Diam. extérieur	222.25 mm
Épaisseur	120.65 mm
Type	GE
Lubrification	sans
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE