


Galet de came avec axe CF12-B-IKO - CF12-B-IKO

<https://www.123roulement.ch/roulement-palier/roulement-bille/galet-came-axe/cf12-b-iko>

IKO

CAM FOLLOWERS

Standard Type Cam Followers **With Cage/With Hexagon Hole**



CF-B

| Stud dia. mm | Identification number | | | | Mass (Ref.) g | D | C | d ₁ | G |
|-----------------|----------------------------|--------------------------------|----------------------------|--------------------------------|---------------------|----|----|----------------|---------|
| | Shield type | | Sealed type | | | | | | |
| | With covered outer ring | With cylindrical outer ring | With covered outer ring | With cylindrical outer ring | | | | | |
| 12 | | CF 12 - B | | | 95 | 30 | 14 | 12 | M12×1.5 |

| Boundary dimensions mm | | | | | | | | | | Mounting dimension f Min. mm | Maximum spinning torque N·m | Basic dynamic load rating C N | Basic static load rating C ₀ N | Maximum allowable static load N |
|------------------------|---------|----------------|----------------|----------------|----------------|----------------|----------------|---|----------------------|--|--------------------------------------|--|--|--|
| G ₁ | B | B ₁ | B ₂ | B ₃ | C ₁ | G ₁ | G ₂ | H | r _s mm | | | | | |
| 13 | 15.2max | 40.2max | 25 | 6 | 0.6 | 6 | 3 | 6 | 0.6 | 21 | 21.9 | 7 910 | 9 790 | 9 790 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3663952442839 |
| Diam. intérieur | 12 mm |
| Diam. extérieur | 30 mm |
| Épaisseur | 14 mm |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE