

Galet de came avec axe CFE12-UU-IKO - CFE12-UU-IKO

<https://www.123roulement.ch/roulement-palier/roulement-bille/galet-came-axe/cfe12-uu-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers **With Cage/With Screwdriver Slot**

Outside diameter of eccentric roller, mm	Identification number				Mass (Ref.)									
	Shield type		Sealed type		\emptyset	D	C	d_2						
16	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	CFE 12 UU	105	30	14	16					
Boundary dimensions, mm														
G	B ₃	B ₁ max	B ₂ max	C ₁	g ₁	G ₁	(¹) Eccentricity e	Mounting dimension f mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N		
M12×1.5	11.5	15.2	40.2	25	0.6	6	13.5	0.6	0.8	21	21.9	7 910	9 790	9 790

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060459916
Diam. intérieur	16 mm
Diam. extérieur	30 mm
Épaisseur	14 mm
Poids	105 g
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE