

Galet de came avec axe CFE16-UU-IKO - CFE16-UU-IKO

<https://www.123roulement.ch/roulement-palier/roulement-bille/galet-came-axe/cfe16-uu-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers **With Cage/With Screwdriver Slot**

Outside diameter of eccentric roller, mm	Identification number				Mass (Ref.)					
	Shield type		Sealed type		\emptyset	D	C	d_2		
22	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	CFE 16	UU	190	35	18	22

Boundary dimensions, mm										Eccentricity e	Mounting dimension f mm	Maximum tightening torque N-m	Basic dynamic load rating C N	Basic static load rating C_0 N	Maximum allowable static load N
G	B_3	B_{max}	B_1 max	B_2	C_1	g_1	G_1	r_{max}	r_{min}						
M16×1.5	15.5	19.6	52.1	32.5	0.8	6	17	0.6	0.8	26	58.5	12 000	18 300	18 300	

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060459985
Diam. intérieur	22 mm
Diam. extérieur	35 mm
Épaisseur	18 mm
Poids	190 g
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE