

Galet de came avec axe CFE18-UUR-IKO - CFE18-UUR-IKO

<https://www.123roulement.ch/roulement-palier/roulement-bille/galet-came-axe/cfe18-uur-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers **With Cage/With Screwdriver Slot**

| Outside diameter of eccentric roller mm | Identification number | | | | Mass (Ref.) | | | |
|---|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------|----|----|----------------|
| | Shield type | | Sealed type | | Ø | D | C | d ₂ |
| | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring | | | | |
| 24 | | | CFE 18 | UUR | 280 | 40 | 20 | 24 |

| Boundary dimensions, mm | | | | | | | | | | Eccentricity g | Mounting dimension f mm | Maximum tightening torque N·m | Basic dynamic load rating C N | Basic static load rating C ₀ N | Maximum allowable static load N |
|-------------------------|----------------|----------|-----------------------|----------------|----------------|----------------|----------------|-------------------------|-----|-------------------|-------------------------------|--|--|--|--|
| G | B ₃ | B max | B ₁ max | B ₂ | C ₁ | g ₁ | G ₁ | (1) r _{max} | e | | | | | | |
| M18×1.5 | 17.5 | 21.6 | 58.1 | 36.5 | 0.8 | 6 | 19 | 1 | 0.8 | 29 | 86.2 | 14 800 | 25 200 | 25 200 | |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3616060460011 |
| Diam. intérieur | 24 mm |
| Diam. extérieur | 40 mm |
| Épaisseur | 20 mm |
| Poids | 280 g |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE