

Galet de came avec axe CFE24-UU-IKO - CFE24-UU-IKO

<https://www.123roulement.ch/roulement-palier/roulement-bille/galet-came-axe/cfe24-uu-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers **With Cage/With Screwdriver Slot**

CFE24-UU

Outside diameter of eccentric roller, mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		ø	D	C	d ₂
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
33				CFE 24 UU	895	62	29	33

Boundary dimensions, mm										Mounting dimension f, mm	Maximum tightening torque, N·m	Basic dynamic load rating, C, N	Basic static load rating, C ₀ , N	Maximum allowable static load, N
G	B ₃	B _{max}	B _{1 max}	B ₂	C ₁	g ₁	G ₁	(1) r _{max}	e					
M24×1.5	25.5	30.6	80.1	49.5	0.8	8	24	1	0.8	40	215	30 500	52 600	52 000

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060460134
Diam. intérieur	33 mm
Diam. extérieur	62 mm
Épaisseur	29 mm
Poids	895 g
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE