


## Galet de came avec axe CFE24-1-UU-IKO - CFE24-1-UU-IKO

<https://www.123roulement.ch/roulement-palier/roulement-bille/galet-came-axe/cfe24-1-uu-iko>

**IKO**  
**CAM FOLLOWERS**  
Eccentric Type Cam Followers **With Cage/With Screwdriver Slot**



CFE24-1-UU

| Outside diameter of eccentric roller mm | Identification number   |                             |                         |                             | Mass (Ref.) |    |    |                |
|---|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------|----|----|----------------|
|   | Shield type             |                             | Sealed type             |                             | Ø           | D  | C  | d <sub>2</sub> |
|   | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring |             |    |    |                |
| 33                                      |                         |                             |                         | <b>CFE 24-1 UU</b>          | 1 220       | 72 | 29 | 33             |

| Boundary dimensions, mm |                |          |                       |                |                |                |                |                         |     | Eccentricity<br>g | Mounting dimension<br>f<br>mm | Maximum<br>tightening<br>torque<br>N·m | Basic dynamic<br>load rating<br>C<br>N | Basic static<br>load rating<br>C <sub>0</sub><br>N | Maximum<br>allowable<br>static load<br>N |
|-------------------------|----------------|----------|-----------------------|----------------|----------------|----------------|----------------|-------------------------|-----|-------------------|-------------------------------|--|--|--|--|
| G                       | B <sub>3</sub> | B<br>max | B <sub>1</sub><br>max | B <sub>2</sub> | C <sub>1</sub> | g <sub>1</sub> | G <sub>1</sub> | (1)<br>r <sub>max</sub> | e   |                   |                               |  |  |  |  |
| M24×1.5                 | 25.5           | 30.6     | 80.1                  | 49.5           | 0.8            | 8              | 24             | 1                       | 0.8 | 40                | 215                           | 30 500                                 | 52 600                                 | 52 000   |  |

### CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | IKO           |
| N° Ean13        | 3663952816524 |
| Diam. intérieur | 33 mm         |
| Diam. extérieur | 72 mm         |
| Épaisseur       | 29 mm         |
| Poids           | 1220 g        |
| Conditionnement | 1             |

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE