

## Galet de came avec axe CR12-BR-IKO - CR12-BR-IKO

<https://www.123roulement.ch/roulement-palier/roulement-bille/galet-came-axe/cr12-br-iko>

**IKO**  
**CAM FOLLOWERS**  
Inch Series Cam Followers With Cage/With Hexagon Hole

CR12-BR

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d <sub>1</sub>	G UNF	G <sub>1</sub>	
	Shield type		Sealed type								
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring							
<b>9.525</b> ( $\frac{3}{8}$ )	<b>CR 12</b>	<b>BR</b>			35	19.050 ( $\frac{3}{4}$ )	12.700 ( $\frac{1}{2}$ )	9.525 ( $\frac{3}{8}$ )	$\frac{1}{4}$ -24	9.525 ( $\frac{3}{8}$ )	
Boundary dimensions mm/inch											
B	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	E <sub>1</sub>	E <sub>2</sub>	H	r	Bearing dimension f Mm/ mm(inch)	Maximum ignoring torque C N-m	Basic static load rating C N	Basic static load rating C <sub>0</sub> N
14.2 (0.56)	22.225 ( $\frac{7}{8}$ )	6.350 ( $\frac{1}{4}$ )	0.794 ( $\frac{1}{32}$ )	4.762 ( $\frac{3}{16}$ )	2.381 ( $\frac{1}{8}$ )	4.762 ( $\frac{3}{16}$ )	0.794 ( $\frac{1}{32}$ )	13.494 ( $\frac{1}{2}$ )	10.8	4 420	5 110

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060462404
Diam. intérieur	9.525 mm
Diam. extérieur	19.05 mm
Epaisseur	12.7 mm
Poids	35 g
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE