

## Galet de came avec axe CR12-BUUR-IKO - CR12-BUUR-IKO

<https://www.123roulement.ch/roulement-palier/roulement-bille/galet-came-axe/cr12-buur-iko>

IKO  
**CAM FOLLOWERS**  
Inch Series Cam Followers With Cage/With Hexagon Hole

CR12-BUUR

| Stud dia.<br>mm<br>(inch)   | Identification number      |                                |                            |                                | Mass<br>(Ref.)<br>g     | D                        | C                        | d <sub>1</sub>                               | G<br>UNF                                    | G <sub>1</sub>                         |  |
|-----------------------------|----------------------------|--------------------------------|----------------------------|--------------------------------|-------------------------|--------------------------|--------------------------|--|---|--|--|
|                             | Shield type                |                                | Sealed type                |                                |                         |                          |                          |  |   |  |  |
|                             | With covered<br>outer ring | With cylindrical<br>outer ring | With covered<br>outer ring | With cylindrical<br>outer ring |                         |                          |                          |  |   |  |  |
| 9.525<br>( $\frac{3}{8}$ )  |                            |                                | CR 12                      | BUUR                           | 35                      | 19.050 ( $\frac{3}{4}$ ) | 12.700 ( $\frac{1}{2}$ ) | 9.525 ( $\frac{3}{8}$ )                      | $\frac{1}{4}$ -24                           | 9.525 ( $\frac{3}{8}$ )                |  |
| Boundary dimensions mm/inch |                            |                                |                            |                                |                         |                          |                          |  |   |  |  |
| B                           | B <sub>2</sub>             | B <sub>3</sub>                 | C <sub>1</sub>             | E <sub>1</sub>                 | E <sub>2</sub>          | H                        | r                        | Bearing<br>dimension<br>f<br>Mm/<br>mm(inch) | Maximum<br>tightening<br>torque<br>C<br>N·m | Basic dynamic<br>load rating<br>C<br>N | Basic static<br>load rating<br>C <sub>0</sub><br>N |
| 14.2 (0.56)                 | 22.225 ( $\frac{7}{8}$ )   | 6.350 ( $\frac{1}{4}$ )        | 0.794 ( $\frac{1}{32}$ )   | 4.762 ( $\frac{3}{16}$ )       | 2.381 ( $\frac{1}{8}$ ) | 4.762 ( $\frac{3}{16}$ ) | 0.794 ( $\frac{1}{32}$ ) | 13.494 ( $\frac{1}{2}$ )                     | 10.8  | 4 420                                  | 5 110  |

### CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | IKO           |
| N° Ean13        | 3616060462428 |
| Diam. intérieur | 9.525 mm      |
| Diam. intérieur | 3/8" inch     |
| Diam. extérieur | 19.05 mm      |
| Diam. extérieur | 3/4" inch     |
| Epaisseur       | 12.7 mm       |
| Epaisseur       | 1/2" inch     |
| Poids           | 35 g          |
| Conditionnement | 1             |

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE