


Galet de came avec axe CR20-B-IKO - CR20-B-IKO

<https://www.123roulement.ch/roulement-palier/roulement-bille/galet-came-axe/cr20-b-iko>

IKO
CAM FOLLOWERS
Inch Series Cam Followers With Cage/With Hexagon Hole



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁	
	Shield type		Sealed type								
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring							
12.700 ($\frac{1}{2}$)	CR 20 B				132	31.750 ($\frac{1}{2}$)	19.050 ($\frac{3}{4}$)	12.700 ($\frac{1}{2}$)	J ₁ -20	15.875 ($\frac{5}{8}$)	
Boundary dimensions mm/inch											
B	B ₂	B ₃	C ₁	E ₁	E ₂	H	r	Bearing dimension f Mm/ mm/inch	Maximum ignoring torque C N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N
20.4100	31.750 ($\frac{1}{2}$)	7.830 ($\frac{5}{16}$)	0.794 ($\frac{1}{16}$)	4.782 ($\frac{3}{8}$)	3.175 ($\frac{1}{4}$)	6.350 ($\frac{1}{4}$)	1.588 ($\frac{1}{16}$)	21.828 ($\frac{7}{8}$)	27.7	14 200	16 000

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060462541
Diam. intérieur	12.7 mm
Diam. extérieur	31.75 mm
Épaisseur	19.05 mm
Poids	132 g
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE