

Galet de came avec axe CR28-BR-IKO - CR28-BR-IKO

<https://www.123roulement.ch/roulement-palier/roulement-bille/galet-came-axe/cr28-br-iko>

IKO
CAM FOLLOWERS
Inch Series Cam Followers With Cage/With Hexagon Hole

CR28-BR

| Stud dia. mm (inch) | Identification number | | | | Mass (Ref.) g | D | C | d ₁ | G UNF | G ₁ |
|-----------------------------|----------------------------|--------------------------------|----------------------------|--------------------------------|---------------------|----------------|-------------|--------------------------------------|---|--|
| | Shield type | | Sealed type | | | | | | | |
| | With covered outer ring | With cylindrical outer ring | With covered outer ring | With cylindrical outer ring | | | | | | |
| 19.050 (3/4) | CR 28 | BR | | | 365 | 44.450 (1 3/4) | 25.400 (1) | 19.050 (3/4) | 7/16 | 22.225 (7/8) |
| Boundary dimensions mm/inch | | | | | | | | | | |
| B | B ₂ | B ₃ | C ₁ | E ₁ | E ₂ | H | r | Bearing dimension f mm/inch | Maximum spinning torque C N·m | Basic static load rating C ₀ N |
| 25.8126 | 44.450 (1 3/4) | 11.112 (3/4) | 0.794 (1/8) | 4.792 (3/4) | 3.969 (3/8) | 7.938 (3/4) | 1.988 (3/8) | 32.543 (1 1/8) | 100 | 25 100 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3616060462640 |
| Diam. intérieur | 19.05 mm |
| Diam. extérieur | 44.45 mm |
| Epaisseur | 25.4 mm |
| Poids | 365 g |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE