

Galet de came avec axe CR8-VUU-IKO - CR8-VUU-IKO

<https://www.123roulement.ch/roulement-palier/roulement-bille/galet-came-axe/cr8-vuu-iko>

IKO
CAM FOLLOWERS
Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



CR--VUU

| Stud dia. mm (inch) | Identification number | | | | Mass (Ref.) | | | | | |
|---------------------------|---|--|---|--|----------------|--------|-------|-------|----------|-------|
| | Shield type With cover With cylindrical outer ring | | Sealed type With cover With cylindrical outer ring | | ϕ | D | C | d_1 | G UNF | G_1 |
| 4.826 | | | | | 9 | 12.700 | 8.731 | 4.826 | No.10-32 | 6.350 |

| Boundary dimensions: mm(inch) | | | | | | | Mounting dimension f Min. mm(inch) | Maximum tightening torque N·m | Basic dynamic load rating C N | Basic static load rating C_0 N |
|-------------------------------|----------------|----------------|----------------|--------------|----------|--------------|--|--|--|---|
| B max | B ₂ | B ₃ | C ₁ | ϕ_1 | ϕ_2 | r | | | | |
| 15.2(0.40) | 12.700(0.50) | - (-) | 0.794(0.031) | 1.175(0.046) | - (-) | 0.387(0.015) | 0.324(0.013) | 1.4 | 4 200 | 4 750 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3616060463111 |
| Diam. intérieur | 4.826 mm |
| Diam. extérieur | 12.7 mm |
| Épaisseur | 8.731 mm |
| Poids | 9 g |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE